



545 Basket Road • Webster, NY 14580  
 Toll Free • 800.691.0292 | Local • 585.265.1990 | Fax • 585.265.6678  
 sales@fastenersdirect.com  
 www.fastenersdirect.com

# KAP TOGGLE ANCHORS



Size	W Toggle Length (Nominal)	Required Hole Size for Base Material	Performance Test Results In Various Materials							
			3/8" Drywall		1/2" Drywall		5/8" Drywall		Masonry Block	
			Pull-Through Load LBS.	Recommend- ed Working Load LBS.	Pull-Through Load LBS.	Recommend- ed Working Load LBS.	Pull-Through Load LBS.	Recommend- ed Working Load LBS.	Pull-Through Load LBS.	Recommend- ed Working Load LBS.
1/8	1.5"	13/32	68	23	111	37	124	41	307	102
3/16	2"	13/32	68	23	115	38	133	44	452	150
1/4	2"	13/32	96	32	121	40	123	41	1091	363



545 Basket Road • Webster, NY 14580  
Toll Free • 800.691.0292 | Local • 585.265.1990 | Fax • 585.265.6678  
[sales@fastenersdirect.com](mailto:sales@fastenersdirect.com)  
[www.fastenersdirect.com](http://www.fastenersdirect.com)

# KAP TOGGLE ANCHORS



**DESCRIPTION:** This is a three-piece anchor that consists of (1) a metal toggle bent at two 90 degree angles with an internally threaded hole at its center, (2) a serrated nylon strap that extends from both sides of the metal toggle, (3) a shoulder washer that slides down the strap and fits snug into the predrilled hole on the front side of the assembly. Upon installation, the extra length of the strap snaps off.

**APPLICATIONS / ADVANTAGES:** Kap Toggle Anchors may be used in hollow wall or masonry block, and re-used multiple times. These anchors have superior pull-out load compared to other hollow wall anchors and they eliminate the need for extra long screws that are sometimes required with other hollow wall anchors. Kap Toggle Anchors are able to be installed by one person.

## MATERIAL:

**TOGGLE:** Cold Rolled Steel

**STRAP & SHOULDER WASHER:** Nylon